

# Product data sheet

## Characteristics

# APDU9966

APC Rack PDU 9000 Switched, ZeroU, 17.3kW,  
208V, (20) C13/C15, (12) C19/C21



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Installation guide Rack mounting brackets Safety guide Serial configuration cable
--------------------	--

### Physical

Cable length	1.83 m
Colour	Black
Depth	7.6 cm
Height	183.3 cm
Net weight	14 kg
Width	11.1 cm

### Input

[In] rated current	48 A
Max line current	48 A
Communication port protocol	SNMP Redfish
Input current limits	60 A
Load capacity	17300 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 60 A 3P + PE
Input voltage	208 V 3 phases

### Output

Number of power socket outlets	20 C13/C15 12 C19/C21
--------------------------------	--------------------------

## Conformance

Product certifications	CUL listed FCC part 15 class A
Standards	IEC 62368-1

## Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Batteries & Runtime

Communication network type	10/100/1000BASE-T Wi-Fi (optional)
----------------------------	---------------------------------------

## Packing Units

Package 1 Weight	19.96 kg
Package 1 Height	214.9 cm
Package 1 width	22.1 cm
Package 1 Length	11.2 cm

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------